







LOCATION OF FUEL TANK

DEVIATIONS FROM THIS LAYOUT COULD RESULT IN ADDITIONAL CHARGES AND/OR DELAYS IN PRODUCTION.

FREIGHTLINER MODEL M2-106 PROFILE DATA CODES

ENGINE

101-2NT CUMMINS ISB 6.7-250

TRANSMISSION

342-582 ALLISON 3000 RDS WITH PTO

343-325 WTEC CALIBRATION - 5 SPEED WITH AUTO NEUTRAL (PACKAGE 180)

84C-022 I. I. 5 - LOW, START, HIGH GEARS - 3K/4K PRIMARY GEARS

> *NO TRANS MOUNTED COOLER OR RETARDER -THESE OPTIONS WILL PROMPT A PTO UPCHARGE.

FRONT AXLE

400-IA6 NON-DRIVING DETROIT DA-F-12.0-3 12.000 LB FFI 71.5 KPI/3.74 DROP SINGLE FRONT **AXLE**

REAR AXLE & SUSPENSION

DETROIT DA-RS-21.0-4 21,000# R-SERIES SINGLE REAR AXLE

3.91 REAR AXLE RATIO 421-391

622-001 23,000 FLAT LEAF SPRING REAR SUSPENSION WITH RADIUS ROD

034-998 NO REAR SUSPENSION PACKAGE

621-001 SPRING SUSPENSION - NO AXI E SPACERS

431-001 STANDARD U-BOLT PADS 439-998 NO REAR SHOCK ABSORBERS

FRAME

 $\frac{11}{32}$ " X 3- $\frac{1}{9}$ " X 10- $\frac{3}{16}$ " STEEL FRAME 120 KSI 546-100 55W-066 FRAME OVERHANG 61-70 INCHES AC8-99D CALC'D BOC TO REAR SUSP. 92.45"

AE8-99D CALC'D BOC TO REAR SUSP. 89.45"

AF4-99D CALC'D FRAME | FNGTH - OVERALL 250 39"

PETERSEN INDUSTRIES REQUIRED FEATURE CODES FOR FREIGHTLINER CHASSIS

204-215, 23U-001 = FUEL TANK

239-001, 237-052 & 016-1C3 = EXHAUST

727-IAF = AIR HORN (NO ROOF MOUNTED HORNS)

460-001 = AIR TANKS (NOTE ON ORDER TO MOUNT TANKS OUTBOARD & PARALLEL TO RH RAIL. MOUNT BRACKETS AT

3450 & 3800)

480-009 & 479-012 = AIR DRYER (IF REQUIRED) =

290-017 & 282-001 = BATTERY BOX

293-058 = CAB MOUNTED BATTERY SWITCH

362-035 = CUSTOMER INSTALLED CHELSEA 277 PTO

372-073 = DASH MOUNTED PTO SWITCH

363-001 = PTO MOUNTED LH SIDE OF TRANS

34C-001 = TRANSMISSION BODY BUILDER CONNECTOR 79K-011 = PTO MODE ENGINE RPM LIMIT 1400 RPM 79L-011 = PTO MODE THRT. OVERRIDE LIMIT TO 1400 RPM

79X-012 = REMOTE PTO SPEED I SETTING 1400 RPM

157-007 = REMOTE ENGINE START/STOP

871 -005 = FNGINF REMOTE INTERFACE

148-073 = ENGINE REMOTE INT. FOR REMOTE THROTTLE

163-001 = FNGINF REMOTE INT CONN BOC

35M-001 = SMARTPLEX HUB MODULE

44R-002 = SMARTPLEX ON/OFF LATCHING = (LAST 3) DIGITS INDICATE # OF SWITCHES, CHANGE TO DESIRED # OF SWITCHES, 2 MINIMUM FOR UPPER TO LOWER CAB, AND STROBE LIGHT)

SMARTPLEX BOOM STOW INDICATOR = 44V-001 OR SMARTPLEX BOOM & OUTRIGGER INDICATOR = 44V-002 INTEGRAL STOP/TAIL/BACKUP LIGHTS = 294-001



PETERSEN INDUSTRIES INC. 4000 S.R. 60 WEST

LAKE WALES, FL. 33859-8234 TEL: (863) 676-1493 FAX: (863) 676-6844

TITLE:

FREIGHTLINER RS3 CHASSIS COMPONENT LOCATIONS

PART NUMBER:

JAC

DRAWN BY:

00 08 04 010 0

NΑ

APPROVED BY: DATE: SHEET: 4/12/2018 I OF I